





- 300 mbps 802.11n access point with 5 dBi antennas
- Standards based WPS simplifies secure WLAN setup
- IPv6 6rd and dual stack support
- Auto detect CenturyLink network setting configuration
- Remote provisioning, monitoring, and management via TR-069
- CenturyLink Standard GUI

## FR1000Z 802.11n Wireless Gateway

## **Benefits**

### **High Speed Broadband Access**

The FR1000Z is based on standards offering fast access to the Internet while maintaining stable connections delivering enough bandwidth to surf the Internet. Heavy multimedia use, such as simultaneously streaming video/audio content and online-gaming, is faster and smoother with the FR1000Z.

#### 802.11n Wireless Technology

The FR1000Z features 802.11n technology with 5 dBi antennas (2T x 2R) which provides the ultimate solution: improved speed, reduced dead zones, and extended coverage. With data rates of up to 300 Mbps, the FR1000Z provides stable and reliable wireless connections for high-speed data and multimedia delivery.

#### **Enhanced Security Features Forms Robust Protection**

Enhanced security ensures the protection of traffic from the WAN to the LAN. Through ZyXEL's implementation of dual Ethernet firewalls (NAT and SPI), the FR1000Z is able to identify and manage malicious content and applications. And, as part of its wireless security design, the FR1000Z supports WPA2/WPA/WEP and features a hardware WPS button allowing customers to enjoy easy setup using a simple button. These features simplify the end user's ability to set up and utilize a secure, wireless network.

#### **TR069 Remote Management**

The FR1000Z provides DSL Forum compliant TR-069 remote management features to ensure faster deployment by Service Providers. In addition, ZyXEL's standard onboard management options, remote provisioning, monitoring, and management features help CenturyLink reduce OPEX while enhancing customer satisfaction.

#### **IPv6 Enabled**

Many North American carrier networks are migrating from IPv4 to IPv4/IPv6 which creates the potential for stranded equipment unable to support these requirements. Certified as an IPv6-ready vendor for over three years, ZyXEL is a global-provider of equipment supporting dual-stack IP networks and provides this feature on many current ZyXEL products, including the FR1000Z.

FR1000Z 802.11n Wireless Gateway















P-060

IPv6

Ethernet

802.11 n 300 Mbps



## FR1000Z **802.11n Wireless Gateway**

## **Specifications**

#### **System Specifications**

#### **WLAN**

- · IEEE 802.11n compliance, backward compatible with 11b/g
- Frequency operation: 2.4 GHz
- 64/128 bits WEP data encryption
- WPA2/WPA (Wi-Fi Protected Access) security
- 4x SSID support
- Wireless scheduler
- Wi-Fi Multimedia (WMM)
- WPS (Wi-Fi Protected Setup)
- WDS
- **MAC Authentication**

#### Router

- NAT
- NAT port forwarding
- Dynamic DNS
- DHCP server/client
- RIP I/RIP II support
- IGMPv1, v2, and v3 support
- **UPnP** support
- QoS
- IPv6 (6rd, dual stack IPv4/IPv6, DHCPv6, PPPv6, Static IPv6)

#### **Firewall**

· Stateful Packet Inspection (SPI)

#### Security

- · Access Scheduler
- Service Blocking
- · Website blocking

#### Management

- Standard CenturyLink GUI
- TR-064
- · TR-069 HTTPS support
- Logs and statistics
- Remote management control: Telnet,
- CLI command via Telnet/console

### **Environmental Specifications**

#### **Operating Environment**

- Temperature: 0°C to 40°C
- Humidity: 20% to 85% RH (Non-condensing)

#### **Storage Environment**

- Temperature: -20°C to 60°C
- Humidity: 20% to 90% RH (Non-condensing)

### **Hardware Specifications**

- Ethernet WAN port (Blue): 1 x RJ-45
- Ethernet LAN port (Yellow): 1 x RJ-45
- Power input (12 V DC 0.5 A)
- USB
- Reset button
- WPS button
- Two 5 dBi external antennas

#### **Physical Specifications**

- Item weight: 1.04 lbs (472 g)
- Item dimensions:
  - 8.3 (L) x 6.1 (W) x 1.7 (H) inch
  - 211 (L) x 155 (W) x 43 (H) mm
- Item and package weight: 2.12 lbs (961 g)
- · Package dimensions:
  - 13.5 (L) x 9.0 (W) x 2.6 (H) inch
  - 342 (L) x 228 (W) x 65 (H) mm

#### Certification

- UL 60950-1
- FCC Part 15 (Class B), Part 68
- WiFi



# Rear panel





